


□ LUCID_R CEILING



78

INSTALLATION

Ceiling version

CONNECTION

Non dimmable luminaires are delivered with 3-pole terminal block
Luminaires for dimming are delivered with 5-pole terminal block

MATERIAL

The body of the luminaire is extruded aluminium, eloxed
or powder coated finish

LIGHT SOURCE

LED Tridonic or TCI, min. 150Lm/W, 3000K or 4000K

DIFFUSER

PMMA OPAL

LIGHT DISTRIBUTION


Direct and sidewalls

EMERGENCY LIGHTING

A unit with integrated emergency is an option

DIMMING

Most models can be delivered dimmable (touch, Dim, DALI)



DIRECT CODE	(mm)	W	Lm from 3000K/4000K
SLRC130	580x78	8	1500/1580
SLRC250	580x78	14	2340/2370
SLRC195	860x78	13	2250/2370
SLRC375	860x78	21	3510/3690
SLRC260	1145x78	16	3000/3160
SLRC500	1145x78	28	4680/4900
SLRC325	1425x78	21	3750/3950
SLRC625	1425x78	35	5850/6150
SLRC2x195	1720x78	26	4500/4740
SLRC2x375	1720x78	42	7000/7380
SLRC2x230	2005x78	29	5250/5530
SLRC2x440	2005x78	49	6510/6860
SLRC2x260	2290x78	32	6000/6320
SLRC2x500	2290x78	56	9360/9800
SLRC2x250	2570x78	36	6750/7110
SLRC2x470	2570x78	63	10530/11025
SLRC2x325	2850x78	42	7500/7900
SLRC2x625	2850x78	70	11700/12300

COLOR TEMPERATURE

3000K	/3K
4000K	/4K

OPTIC

PMMA OPAL	/--
-----------	-----

DIMMABLE OPTIONS

DALI, TOUCHDIM	/DALI	see page 223
WIRELESS	/WRS	see page 223

COLORS

	WHITE	/WH
	BLACK	/BL
	SILVER	/SI
	ANTRACIT	/AT
	GOLD	/GL
	BRONZE	/BR

