

□ BELO_BE_SQ_80 CEILING



INSTALLATION

Ceiling version

CONNECTION

Non dimmable luminaires are delivered with 3-pole terminal block
Luminaires for dimming are delivered with 5-pole terminal block

MATERIAL

The body of the luminaire is curved extruded aluminium,
powder coated finish

LIGHT SOURCE

LED Tridonic or TCI, min. 150Lm/W, 3000K or 4000K

DIFFUSER

PMMA OPAL
PRISMATIC

LIGHT DISTRIBUTION


Direct symmetrical
Direct symmetrical / Passive indirect symmetrical

EMERGENCY LIGHTING



A unit with integrated emergency is an option

DIMMING

Most models can be delivered with ballast
for dimming (TOUCHDIM, DALI)



80 



| DIRECT CODE | (mm) | W | Lm from 3000K/4000K |
|------------------|------------|----|---------------------|
| SBC/80/BE/SQ/330 | 330x330x50 | 8 | 1340/1400 |
| SBC/80/BE/SQ/570 | 570x570x50 | 32 | 5360/5600 |
| SBC/80/BE/SQ/850 | 850x850x50 | 72 | 11160/12600 |

| DIRECT/INDIRECT CODE | (mm) | W | Lm from 3000K/4000K |
|----------------------|------------|----|---------------------|
| CODE | 330x330x50 | 8 | 1340/1400 |
| SBC/80/BE/SQ/570/DI | 570x570x50 | 32 | 5360/5600 |
| SBC/80/BE/SQ/850/DI | 850x850x50 | 72 | 11160/12600 |

COLOR TEMPERATURE

| | |
|-------|-----|
| 3000K | /3K |
| 4000K | /4K |

OPTIC

| | |
|-----------|-----|
| PMMA OPAL | /-- |
| PRISMATIC | /P |

DIMMABLE OPTIONS

| | |
|----------------|-------|
| DALI, TOUCHDIM | /DALI |
| WIRELESS | /WRS |

COLORS

| | | |
|--|----------|-----|
|  | WHITE | /WH |
|  | BLACK | /BL |
|  | SILVER | /SI |
|  | ANTRACIT | /AT |
|  | GOLD | /GL |
|  | BRONZE | /BR |

