

# □ BELO\_QA\_110 SUSPENDED



## INSTALLATION

Suspended version

## CONNECTION

Non dimmable luminaires are delivered with 3-pole terminal block  
Luminaires for dimming are delivered with 5-pole terminal block

## MATERIAL

The body of the luminaire is curved extruded aluminium,  
powder coated finish

## LIGHT SOURCE

LED Tridonic or TCI, min. 150Lm/W, 3000K or 4000K

## DIFFUSER

PMMA OPAL  
PRISMATIC

## LIGHT DISTRIBUTION

Direct symmetrical  
Direct symmetrical / Passive indirect symmetrical

## EMERGENCY LIGHTING



A unit with integrated emergency is an option

## DIMMING

Most models can be delivered with ballast  
for dimming (TOUCHDIM, DALI)




110



DIRECT CODE	(mm)	W	Lm from 3000K/4000K
SBS/110/QA/330	330x330x50	8	1340/1400
SBS/110/QA/570	570x570x50	32	5360/5600
SBS/110/QA/850	850x850x50	72	11160/12600

DIRECT/INDIRECT CODE	(mm)	W	Lm from 3000K/4000K
SBS/110/QA/330/DI	330x330x50	8	1340/1400
SBS/110/QA/570/DI	570x570x50	32	5360/5600
SBS/110/QA/850/DI	850x850x50	72	11160/12600

Delivered incl. 2 m self-locking suspensions



**COLOR TEMPERATURE**

3000K	/3K
4000K	/4K

**OPTIC**

PMMA OPAL	/--
PRISMATIC	/P

**DIMMABLE OPTIONS**

DALI, TOUCHDIM	/DALI
WIRELESS	/WRS

**COLORS**

	WHITE	/WH
	BLACK	/BL
	SILVER	/SI
	ANTRACIT	/AT
	GOLD	/GL
	BRONZE	/BR

	75	SPPKB3075 (3X0,75)
	75	SPPKB5075 (5X0,75)
	75	TRANSPARENT CABLE 2 METRES WITH CEILING BOX
	25	