

□ CUBUS_R CEILING



ARCHILIGHT

140



80



600

900

1200

1500



INSTALLATION

Ceiling version

CONNECTION

Non dimmable luminaires are delivered with 3-pole terminal block
Luminaires for dimming are delivered with 5-pole terminal block

MATERIAL

The body of the luminaire is curved extruded aluminium, powder coated finish

LIGHT SOURCE

LED Tridonic or TCI, min. 150Lm/W, 3000K or 4000K

DIFFUSER

PMMA OPAL
PRISMATIC

LIGHT DISTRIBUTION

Direct symmetrical

EMERGENCY LIGHTING

A unit with integrated emergency is an option

DIMMING

Most models can be delivered with ballast for dimming (TOUCHDIM, DALI)

DIRECT CODE	(mm)	W	Lm from 3000K/4000K
SCCR130	600x90x80	16	2680/2840
SCCR250	600x90x80	24	3720/3920
SCCR195	900x90x80	26	4020/4260
SCCR375	900x90x80	37	5580/5880
SCCR260	1200x90x80	33	5360/5680
SCCR500	1200x90x80	49	7440/7840
SCCR325	1500x90x80	41	6700/7100
SCCR625	1500x90x80	61	9300/9800

COLOR TEMPERATURE

3000K /3K
4000K /4K

OPTIC

PMMA OPAL /--
PRISMATIC /P

DIMMABLE OPTIONS

DALI, TOUCHDIM /DALI
WIRELESS /WRS

COLORS

	WHITE	/WH
	BLACK	/BL
	SILVER	/SI
	ANTRACIT	/AT
	GOLD	/GL
	BRONZE	/BR