

□ CUBUS_S SUSPENDED



ARCHILIGHT

35



80

INSTALLATION

Suspended version

CONNECTION

Non dimmable luminaires are delivered with 3-pole terminal block
Luminaires for dimming are delivered with 5-pole terminal block

MATERIAL

The body of the luminaire is extruded aluminium,
powder coated finish

LIGHT SOURCE

LED Tridonic or TCI, min. 150Lm/W, 3000K or 4000K

DIFFUSER

PMMA OPAL
PRISMATIC

LIGHT DISTRIBUTION

Direct symmetrical

EMERGENCY LIGHTING

A unit with integrated emergency is an option

DIMMING

Most models can be delivered with ballast
for dimming (TOUCHDIM, DALI)



COLOR TEMPERATURE

3000K /3K
4000K /4K

OPTIC

PMMA OPAL /--
PRISMATIC /P

DIMMABLE OPTIONS

DALI, TOUCHDIM /DALI
WIRELESS /WRS

COLORS

	WHITE	/WH
	BLACK	/BL
	SILVER	/SI
	ANTRACIT	/AT
	GOLD	/GL
	BRONZE	/BR

DIRECT CODE	(mm)	W	Lm from 3000K/4000K
SCSS90	850x35x80	13	2010/2130
SCSS120	1135x35x80	17	2680/2840
SCSS150	1415x35x80	21	3350/3550

Delivered incl. 2 m self-locking suspensions

ACCESSORIES

- 80 SCSSPKK END CAP 2PCS
- 75 SPPKBO3075 (3X0,75)

 75 SPPKBO5075 (5X0,75)
 TRANSPARENT CABLE 2 METRES WITH CEILING BOX
- 25

