

□ CUBUS SQUARE SUSPENDED





## INSTALLATION

Suspended version

## CONNECTION

Non dimmable luminaires are delivered with 3-pole terminal block  
Luminaires for dimming are delivered with 5-pole terminal block

## MATERIAL

The body of the luminaire is extruded aluminium, powder coated finish

## LIGHT SOURCE

LED Tridonic or TCI, min. 150Lm/W, 3000K or 4000K

## DIFFUSER

PMMA OPAL  
PRISMATIC

## LIGHT DISTRIBUTION

Direct symmetrical

## EMERGENCY LIGHTING

A unit with integrated emergency is an option

## DIMMING

Most models can be delivered with ballast for dimming (TOUCHDIM, DALI)

## COLOR TEMPERATURE

3000K /3K  
4000K /4K

## OPTIC

PMMA OPAL /--  
PRISMATIC /P



## DIMMABLE OPTIONS

DALI, TOUCHDIM /DALI  
WIRELESS /WRS

## COLORS

	WHITE	/WH
	BLACK	/BL
	SILVER	/SI
	ANTRACIT	/AT
	GOLD	/GL
	BRONZE	/BR

## ACCESSORIES

	75	SPPKBO3075 (3X0,75) SPPKBO5075 (5X0,75) TRANSPARENT CABLE 2 METRES WITH CEILING BOX
	25	

DIRECT CODE	(mm)	W	Lm from 3000K/4000K
SCSQ130	630x630x62	33	5360/5680
SCSQ195	915x915x62	49	8040/8520

Delivered incl. 2 m self-locking suspensions

