

□ CUBUS_XL SUSPENDED



INSTALLATION

Suspended version

CONNECTION

Non dimmable luminaires are delivered with 3-pole terminal block
Luminaires for dimming are delivered with 5-pole terminal block

MATERIAL

The body of the luminaire is extruded aluminium, powder coated finish

LIGHT SOURCE

LED Tridonic or TCI, min. 150Lm/W, 3000K or 4000K

DIFFUSER

PMMA OPAL
PRISMATIC

LIGHT DISTRIBUTION

Direct symmetrical
Direct symmetrical / Passive indirect symmetrical,


EMERGENCY LIGHTING

A unit with integrated emergency is an option

DIMMING

Most models can be delivered with ballast for dimming (TOUCHDIM, DALI)

ARCHILIGHT





DIRECT CODE	(mm)	W	Lm from 3000K/4000K
SCSXL60	595x70x80	9	1340/1420
SCSXL90	850x70x80	13	2010/2130
SCSXL120	1135x70x80	17	2680/2840
SCSXL150	1415x70x80	21	3350/3550
SCSXL170	1700x70x80	26	4020/4260
SCSXL200	1980x70x80	29	4690/4970
SCSXL230	2265x70x80	33	5360/5680
SCSXL280	2825x70x80	41	6700/7100

DIRECT/ INDIRECT CODE	(mm)	W	Lm from 3000K/4000K
SCSXL60/DI	595x70x80	9	1340/1420
SCSXL90/DI	850x70x80	13	2010/2130
SCSXL120/DI	1135x70x80	17	2680/2840
SCSXL150/DI	1415x70x80	21	3350/3550
SCSXL170/DI	1700x70x80	26	4020/4260
SCSXL200/DI	1980x70x80	29	4690/4970
SCSXL230/DI	2265x70x80	33	5360/5680
SCSXL280/DI	2825x70x80	41	6700/7100

Delivered incl. 2 m self-locking suspensions

COLOR TEMPERATURE

3000K /3K
4000K /4K

OPTIC

PMMA OPAL /--
PRISMATIC /P

DIMMABLE OPTIONS

DALI, TOUCHDIM /DALI
WIRELESS /WRS

COLORS

WHITE	/WH
BLACK	/BL
SILVER	/SI
ANTRACIT	/AT
GOLD	/GL
BRONZE	/BR

ACCESSORIES

70	SCXLPKK END CAP 2PCS
----	----------------------------

75	SPPKBO3075 (3X0,75) SPPKBO5075 (5X0,75) TRANSPARENT CABLE 2 METRES WITH CEILING BOX
----	--

