


□ DOWNLIGHT RECESSED



ARCHILIGHT



DIRECT CODE	(mm)	W	Lm from 3000K/4000K
SKV/100/1000/60°	100	11	1060/1110
SKV/100/1000/90°	100	11	1060/1110
SKV/150/1000/60°	150	11	1060/1110
SKV/150/1000/90°	150	11	1060/1110
SKV/150/2000/60°	150	22	2130/2210
SKV/150/2000/90°	150	22	2130/2210
SKV/200/2000/60°	200	22	2130/2210
SKV/200/2000/90°	200	22	2130/2210
SKV/200/3000/60°	200	32	3070/3180
SKV/200/3000/90°	200	32	3070/3180

INSTALLATION

Recessed version

CONNECTION

Non dimmable luminaires are delivered with 3-pole terminal block
Luminaires for dimming are delivered with 5-pole terminal block

MATERIAL

The body of the luminaire is extruded aluminium, powder coated finish

LIGHT SOURCE

LED Tridonic

REFLECTOR

60° and 90°

LIGHT DISTRIBUTION

Direct symmetrical

DIMMING

Most models can be delivered with ballast for dimming (TOUCHDIM, DALI)

COLOR TEMPERATURE

3000K /3K
4000K /4K

OPTIC

PMMA OPAL /--
PRISMATIC /P

DIMMABLE OPTIONS

DALI, TOUCHDIM /DALI
WIRELESS /WRS

COLORS

WHITE /WH