


# □ LUCID\_R SUSPENDED



78

## INSTALLATION

Suspended version

## CONNECTION

Non dimmable luminaires are delivered with 3-pole terminal block  
Luminaires for dimming are delivered with 5-pole terminal block

## MATERIAL

The body of the luminaire is extruded aluminium, eloxed  
or powder coated finish

## LIGHT SOURCE

LED Tridonic or TCI, min. 150Lm/W, 3000K or 4000K

## DIFFUSER

PMMA OPAL

## LIGHT DISTRIBUTION


Direct and sidewalls

## EMERGENCY LIGHTING

A unit with integrated emergency is an option

## DIMMING

Most models can be delivered dimmable (touch, Dim, DALI)



DIRECT CODE	(mm)	W	Lm from 3000K/4000K
SLRS130	580x78	8	1500/1580
SLRS250	580x78	14	2340/2370
SLRS195	860x78	13	2250/2370
SLRS375	860x78	21	3510/3690
SLRS260	1145x78	16	3000/3160
SLRS500	1145x78	28	4680/4900
SLRS325	1425x78	21	3750/3950
SLRS625	1425x78	35	5850/6150
SLRS2x195	1720x78	26	4500/4740
SLRS2x375	1720x78	42	7000/7380
SLRS2x230	2005x78	29	5250/5530
SLRS2x440	2005x78	49	6510/6860
SLRS2x260	2290x78	32	6000/6320
SLRS2x500	2290x78	56	9360/9800
SLRS2x250	2570x78	36	6750/7110
SLRS2x470	2570x78	63	10530/11025
SLRS2x325	2850x78	42	7500/7900
SLRS2x625	2850x78	70	11700/12300

Delivered incl. 2 m self-locking suspensions

#### COLOR TEMPERATURE

3000K /3K  
4000K /4K

#### OPTIC

PMMA OPAL /--

#### DIMMABLE OPTIONS

DALI, TOUCHDIM /DALI see page 223  
WIRELESS /WRS see page 223

#### COLORS

	WHITE	/WH
	BLACK	/BL
	SILVER	/SI
	ANTRACIT	/AT
	GOLD	/GL
	BRONZE	/BR

#### ACCESSORIES

	75	SPPKBO3075 (3X0,75)
	75	SPPKBO5075 (5X0,75)
	25	TRANSPARENT CABLE 2 METRES WITH CEILING BOX

