

□ LUCID WALL



ARCHILIGHT

INSTALLATION

Wall version

CONNECTION

Non dimmable luminaires are delivered with 3-pole terminal block

Luminaires for dimming are delivered with 5-pole terminal block

MATERIAL

The body of the luminaire is extruded aluminium, eloxed finish

LIGHT SOURCE

LED Tridonic or TCI, min. 150Lm/W, 3000K or 4000K

DIFFUSER

PMMA OPAL
PRISMATIC

LIGHT DISTRIBUTION


Direct symmetrical
Direct symmetrical / active indirect symmetrical

EMERGENCY LIGHTING

A unit with integrated emergency is an option


DIMMING

Most models can be delivered with ballast for dimming (TOUCHDIM, DALI)



DIRECT CODE	(mm)	W	Lm from 3000K/4000K
SLW130	585x57x70	8	1500/1580
SLW250	585x57x70	14	2340/2450
SLW195	860x57x70	13	2250/2370
SLW375	860x57x70	21	3510/3690
SLW260	1145x57x70	16	3000/3160
SLW500	1145x57x70	28	4680/4900
SLW325	1425x57x70	21	3750/3950
SLW625	1425x57x70	35	5850/6150
SLW2x195	1710x57x70	26	4500/4740
SLW2x375	1710x57x70	42	7000/7380
SLW2x230	1990x57x70	29	5250/5530
SLW2x440	1990x57x70	49	8190/8610
SLW2x260	2280x57x70	32	6000/6320
SLW2x500	2280x57x70	56	9360/9800
SLW2x325	2840x57x70	42	7500/7900
SLW2x625	2840x57x70	70	11700/12300

ACCESSORIES



COLOR TEMPERATURE

3000K /3K
4000K /4K

OPTIC

PMMA OPAL /--

DIMMABLE OPTIONS

DALI, TOUCHDIM /DALI
WIRELESS /WRS

COLORS

ELOX /..